

*National Conference on Emerging Trends in Arts, Humanities and
Multidisciplinary Research (NCETAHMR)*

Organized by- Navyug College of Education, Hisar (16 Aug 2026)

In IJESH ISSN: 2250-3115

**Integrated Satellite Communication Framework for Improving Digital
Access and Service Delivery in Rural and Remote Regions**

Preeti Sindhu

Research Scholar, Department of Computer Science and Applications, Baba Mastnath University,
Asthal Bohar, Rohtak, Haryana, India

Dr. Neha Gaba

Associate Professor, Department of Computer Science and Applications, Baba Mastnath University,
Asthal Bohar, Rohtak, Haryana, India

Abstract

The aim of this research paper is to create an integrated satellite communication system to enhance digital access and service in rural and remote areas. The study builds on the latest research in the areas of satellite broadband, 3GPP non-terrestrial networks (NTN), high throughput satellites, low Earth orbit constellations, satellite backhaul, direct-to-device connectivity, satellite Internet of Things (IoT), and rural digital-inclusion policy. It states that rural connectivity must not be viewed as a single satellite connectivity arrangement; instead, it needs to be shaped as a multi-layer service architecture that includes space, transport, local access, edge computing, energy, service platforms and governance. The proposed framework involves the selective use of GEO, MEO and LEO capacity; satellite integration with fibre, microwave, 4G/5G, Wi-Fi, fixed wireless and LPWAN; and education, healthcare, agriculture, e-government, disaster response and local enterprise services are the priority areas. Three analytical tables are provided to compare technology options, to define the integrated framework and to map the requirements for delivering services to the appropriate connectivity strategies. The analysis reveals that hybrid terrestrial–satellite networks can mitigate the “geographic penalty” of sparsely populated regions, but only if they are affordable, power reliable, local maintenance is available, spectrum and licensing policies are appropriate, cyber security is not an issue, communities are involved, and measurable obligations for service quality are established. The paper argues that an integrated and service-aware architecture is more sustainable than a single-technology approach, as it can optimize traffic, cost, latency, energy, and resilience all together, and remain flexible with the development of new NTN standards and direct-device ecosystems.

Keywords: satellite communication; rural connectivity; remote regions; digital access; service delivery; non-terrestrial networks; LEO; satellite backhaul; 5G-NTN; digital inclusion

Introduction

Digital inequality is growing and is an expression of the cost of distance. Urban broadband networks have high population density, short distances to reach customers, good power supply, long fibre routes and existing towers, while remote areas may have low population density with mountainous areas, islands, deserts, forests, seasonal roads and weak power supply. In these cases, the marginal benefit of extending terrestrial networks increases quickly as a function of additional site added and the per-site revenue remains modest. The International Telecommunication Union (ITU) defines rural and

National Conference on Emerging Trends in Arts, Humanities and Multidisciplinary Research (NCETAHMR)

Organized by- Navyug College of Education, Hisar (16 Aug 2026)

In IJESH ISSN: 2250-3115

remote connectivity as a multidimensional challenge, where infrastructure, affordability, quality of service, sustainable business models, energy and universal-service mechanisms are not independent concepts, but are interdependent (ITU, 6). Satellite systems are thus important not just for the area they can cover, but because they can circumvent many of the linear construction costs which make terrestrial expansion uneconomic. The current satellite constellation is significantly different from the typical one consisting of a limited number of geostationary communication satellites. The advantage of high throughput satellites is that they have a capacity boost from using spot beams and frequency reuse, while LEO satellites offer a reduction in propagation distance and improved interactive performance. Digital payloads and SDN technologies offer a capacity flexibility through the use of reconfigurable resources and Inter-Satellite Links (ISLs) reduce dependence on specific ground gateways. Kodheli et al. call this shift a 'new space' era, in which the architecture of satellite systems, air interfaces, networking, payload design, and terrestrial integration are all being rethought. This change will provide a better underpinning to rural broadband; however, it also introduces more challenges for network planning as the planner will have to deal with the choice of the different orbit classes, bands, operators, terminal types, and service models. The standardization of networks on the airplane is further reinforced by the non-terrestrial network standardization. 3GPP Release 17 encompasses significant technical aspects for 5G NR and cellular IoT use over satellite links, such as compensation for Doppler effect, long propagation delay, timing relationship, moving beams, mobility, and network architecture. Lin et al. discuss the integration of NTN not as a single radio-interface change, but as an integrated sequence of changes in user equipment, radio access, core network, mobility and service procedures, (Lin et al., 153). The convergence is important for rural areas, where satellite access may eventually be integrated into the rural communications infrastructure rather than a niche network.

The satellite and mobile systems are also gaining ground in the current policy discussion as complementary systems. As described in the Broadband Commission's State of Satellite Broadband 2025, satellite-based communications are increasingly playing a part with mobile communications in connecting remote and rural areas and filling in underserved spaces, while other models of NTN are also gaining popularity, including the direct-to-cell service (Broadband Commission, 10). This evolution will alter the fundamental planning question. The question is no longer about the use of terrestrial or satellite connections for rural access but how different communication layers work together so each service is carried through the most appropriate layer at an acceptable cost, reliability and satisfaction level. Access to digital resources is only useful if it allows for meaningful activity, which means a service-delivery perspective is crucial. Rural users need connectivity to school, hospital, farm advice, market information, financial transactions, government information, warnings, logistics, remote working and for communicating within the community. The traffic pattern of these applications is very different. A soil sensor can send a few bytes every so often and tolerate delay, and a medical consultation from a remote location needs stable two-way video, acceptable latency, no jitter and reliable uplink. This paper's framework is therefore service-aware, whereby connectivity

National Conference on Emerging Trends in Arts, Humanities and Multidisciplinary Research (NCETAHMR)

Organized by- Navyug College of Education, Hisar (16 Aug 2026)

In IJESH ISSN: 2250-3115

is allocated based on application needs and not tried to be universally applied to all rural users with the same network profile.

The research problem this paper addresses is one related to the evaluation of rural satellite projects at just one layer. Engineering studies could be on an orbit or link performance; policy programs could be on coverage counts or installed terminals. However, there are many other areas in which a rural service can fall short: local WiFi may be congested; batteries may be too small; maintenance may need to be done in expensive off-site locations; tariffs may be too high to pay; gateways may be poorly redundant; users may not have devices that comply with the service. The systematic review of satellite Internet conducted by Chen, Ma, and Wu revealed that the research area extends beyond architecture and applications to the technical functions and to a social impact, indicating the need for integrative analysis and not only optimization (Chen, Ma, 4). This brief paper sets out to create a satellite communication integration that combines technical architecture and digital access and public service delivery. What will be the mix of satellite, terrestrial, local-access, edge and energy resources required to provide sustainable connectivity in remote areas? (2) What is the mapping between rural service classes to network performance, cost and resilience requirements? (3) What governance and operational settings are required to make technical coverage an effective digital inclusion? The paper uses research synthesis and design-science reasoning to respond to these questions and segments the final topology into interoperable layers instead of a single vendor-specific topology.

The novelty of this paper is the approach of considering connectivity, public-service delivery and sustainability as one design problem. The framework enables GEO, MEO, and LEO resources to coexist; allows terrestrial fibre or microwave to be the main mode of transport where possible; enables satellite backhaul to community access services; provides direct to device capability for continuity of service and emergencies; provides local caching and edge processing to relieve backhaul load; and provides the same planning considerations to energy, cybersecurity, maintenance, and policy as throughput and latency. This type of building is especially well adapted to areas where the economic and geographic conditions differ greatly from one settlement to another.

Research Methodology

This paper is written in a method of structured research-synthesis. The evidence base includes peer-reviewed survey papers, standards-oriented research, recent field studies, performance of LEO and GEO, rural backhaul, digital inclusion, and regulatory design reports on satellite Internet, 5G/6G NTN, satellite IoT, etc. Presented findings are then transformed into an integrated architecture using design-science reasoning. An appropriate approach is taken as the research goal is not to estimate a single statistical relationship but determine what components interact to make a remote connectivity system an end-to-end service or not. Also, Chen, Ma, and Wu find that the study of satellite Internet is multiscientific and encompasses aspects such as application, enabling technology and impact areas (Chen, 4). The framework is followed by five conceptual principles. The first is the complementary principle: networks (satellite and terrestrial) should not be seen as mutually exclusive options. The second is service awareness: various applications should have different latencies, throughput, availability and priority treatment. The third is aggregation: If the economics of household networks

National Conference on Emerging Trends in Arts, Humanities and Multidisciplinary Research (NCETAHMR)

Organized by- Navyug College of Education, Hisar (16 Aug 2026)

In IJESH ISSN: 2250-3115

are weak, village backhaul can be shared among a number of users. The fourth is resilience: critical sites need path diversity, local cache and power autonomy. The fifth is life-cycle sustainability – capital cost, recurring capacity, licensing, energy, local support, spares, cybersecurity updates, and terminal replacement are all factors to be taken into account during project evaluation, not just capital cost.

Coverage vs usable service is a fundamental difference. Despite technically covering a village, users might still have an unusable experience due to obstruction, rain fade, local congestion, inadequate WiFi placement, device incompatibility, broken electrical power, or weak backhaul capacity. That's why end-to-end metrics are needed. The network should not only measure the quality of the satellite signal, but also the throughput of the users, the stability of the uplink, the jitter, the utilization of local access, the energy state, the availability of the gateway, and the response time of the application. To enable sustainable digital inclusion, satellite Internet should fill the performance and management gaps that have been identified (Hu, 5). Orbit selection problem is formulated as a multi-objective problem. Advantages of GEO systems are large footprints, constant visibility from a fixed point, mature infrastructure, efficient broadcast and backhaul, but there is high latency due to propagation distance. Although LEO systems are capable of having low propagation delay, they tend to have a lot of handovers, moving beams, tracking complexity and require large constellation operations for good broadband performance. MEO systems fall somewhere in between. Satellite performance is not just the result of orbit but is a result of the interplay of architecture, air interface, medium access, payload design, routing, and ground systems (Kodheli et al., 99).

Table 1. Comparative Role of Major Connectivity Technologies in Remote and Rural Networks

Technology	Principal strength	Principal limitation	Best integrated role
GEO satellite	Very wide persistent coverage; mature backhaul	High propagation latency	Bulk backhaul, broadcast, fallback, wide-area coverage
MEO satellite	Intermediate latency and footprint	Smaller commercial ecosystem in some regions	Regional broadband and multi-orbit diversity
LEO satellite	Lower latency; high broadband potential	Handover, moving beams, constellation dependence	Interactive broadband, mobile backhaul, low-latency services
4G/5G terrestrial	Strong device ecosystem; mobility	Tower and backhaul economics in sparse areas	Local/mobile access where population density supports it

**National Conference on Emerging Trends in Arts, Humanities and
Multidisciplinary Research (NCETAHMR)**

Organized by- Navyug College of Education, Hisar (16 Aug 2026)

In IJESH ISSN: 2250-3115

Wi-Fi/FWA	Low-cost local distribution	Limited range and backhaul dependence	Village distribution behind satellite or fibre backhaul
Satellite IoT/LPWAN	Low power; very wide sensor coverage	Low throughput	Agriculture, environment, asset and utility monitoring

Source: Research synthesis based on Kodheli et al., 109

The framework also provides for separating the categories of household broadband, community backhaul, mobile backhaul, institutional connectivity, direct-to-device service and sensor connectivity. These are not the same use cases that are economically equivalent. For a clinic or school, a dedicated terminal may be more appropriate, depending on the criticality of service; a compact village can be much lower cost per user on a single satellite gateway connected to Wi-Fi or a cellular small cell; isolated farms may require dedicated broadband; and agricultural sensors may only need satellite IoT. Rural connectivity models can include community networks based on satellite backhaul and local distribution technologies, which can help to distance the more expensive long-distance link from the more lower-cost local access layer (ITU, 17). Research evaluation is done on the basis of engineering and inclusion. Latency, throughput, jitter, packet loss, availability, handover interruption, energy consumption, gateway diversity, and recovery time are a few engineering measures. Monthly cost as percentage of income, number of users per shared access point, service adoption, device compatibility, language accessibility, uptime of public service sites and number of locally trained maintainers are examples of measures of inclusion. Renewable energy, community participation, sustainable business models and universal-service mechanisms are explicitly mentioned in the ITU guidance on rural connectivity, making it clear that infrastructure is not enough to count as a success (ITU, 33). The framework is then theoretic but application to empirical level. Each layer can be filled with measurable variables and alternative configurations can be compared. The primary challenges can vary from mountainous areas to islands, from desert areas to farming areas, and on islands, they may be gateway diversity and transport cost, in mountainous areas obstruction, and in desert areas energy and thermal management may be the primary challenges and in farming areas the challenge may be to cover vast areas with low-cost IoT and also support a smaller number of broadband sites. These differences can all be accommodated in the same framework without postulating per se that one orbit, operator and access technology is always the best.

Proposed Integrated Satellite Communication Framework

The proposed architecture is organised in seven interrelated layers: space resources, transport and gateway infrastructure, local access, edge and service platforms, energy and physical infrastructure, operations and security, governance and affordability. The seven layers are orchestrated by a 'cross-layer orchestration function' with real-time data on service priorities, congestion, latency, pricing, energy state, security state and link availability. This is intentionally a more general architecture than a conventional network stack, since the success of remote-service relies on conditions that are often outside the scope of traditional protocol design including physical, operational and institutional


National Conference on Emerging Trends in Arts, Humanities and Multidisciplinary Research (NCETAHMR)

Organized by- Navyug College of Education, Hisar (16 Aug 2026)

In IJESH ISSN: 2250-3115

conditions. It may be GEO, MEO, LEO or multi-orbit. The main function of this layer is to give geographic reach and capacity without the need for continuous infrastructure between the user area and the rest of the network. LEO can be used for delay sensitive applications and high performance broadband; GEO for bulk transfer, broadcast, stable wide area backhaul and resilient fallback; MEO for regional capacity with medium delay characteristics. The satellite broadband and NTN technology is rapidly proliferating as part of a larger trend of providing access to underserved areas using a combination of space-based and mobile-based systems to reach these areas (Broadband Commission, 10). The transport and gateway layer connects satellite resources with Internet peering, cloud platforms, mobile cores, and public sector networks. These are the feeder links, ground gateways, terrestrial fibre, microwave, inter-satellite links and routing systems. The diversity of gateway is important as satellite service may still be unavailable if one gateway on the ground or a terrestrial path is unavailable. The framework thus recommends geographic gateway redundancy for critical areas, dynamic routing over available paths and inter-satellite transport when available. This transforms satellite transmission into a robust end-to-end connectivity, instead of a single point of failure. Local-access layer: Provides connectivity to households, institutions, farms and devices from an aggregation point. Satellite backhauls can support Wi-Fi, 4G/5G small cells, FWA, PMP, and LPWAN. This design is economically significant as it can save the number of satellite terminals needed, due to community aggregation. A village can be served by one or more high capacity satellite link and users can access them with small and low cost devices that they already own. It can enable prepaid access, public Wi-Fi hotspots, school networks, priority traffic for clinics, and enterprise service tiers.

Image 1: Proposed Seven-Layer Integrated Satellite Communication Framework for Rural and Remote Regions



***National Conference on Emerging Trends in Arts, Humanities and
Multidisciplinary Research (NCETAHMR)***

Organized by- Navyug College of Education, Hisar (16 Aug 2026)

In IJESH ISSN: 2250-3115

Direct-to-device/direct-to-cell connectivity provides a parallel local-access option that is not an alternative to shared broadband. D2D is particularly useful in early rural deployments for emergency messaging, voice, low-rate data, alerts, location reporting and sensor connectivity, in the absence of any terrestrial cell. Direct-to-cell is an area of emerging satellite–mobile convergence identified by the State of Satellite Broadband 2025 and its potential in rural and underserved areas (Broadband Commission, 12). The framework thus leverages D2D to provide continuity and safety while keeping high volume shared services' own broadband terminals.

The edge and service-platform layer enhances not only user experience, but also bandwidth efficiency. Local caching of frequently used Web objects such as educational videos, health information, software updates, agricultural topics, government forms, maps, and more. Edge systems can additionally control authentication, local DNS, learning platforms, farm analytics, content material screening (when legally required), and security checking. In the event that the satellite backhaul becomes unavailable, the school/clinic can access locally hosted resources and synchronize the data with the satellite backhaul when it becomes available. Such the capacity for working through discontinuous backhaul is vital for effective delivery in rural areas.

The energy and physical-infrastructure layer helps to solve a key challenge for rural networks: access to unreliable power and challenging maintenance. Clean and continuous power is required for satellite terminals, routers, access points, small cells, switches, edge servers and batteries. ITU guidance on rural connectivity focuses on renewable energy sources, including solar energy, as viable solutions for remote ICT infrastructure facing challenges with grid extension or high costs (ITU, 30). In the framework, the state of the battery is an operational variable. Non-critical synchronization can be postponed, secondary radios can be put into low-power modes, and critical traffic can be protected during low-energy time.

Table 2. Integrated Satellite Communication Framework for Rural and Remote Service Delivery

Layer	Core elements	Primary objective	Key planning variables	Author(s) & Year
Space resources	GEO/MEO/LEO, beams, ISLs	Coverage and non-terrestrial capacity	Latency, throughput, footprint, weather, cost	Kodheli et al. (2021)
Transport & gateways	Gateways, fibre, microwave, routing	Reach Internet/mobile core reliably	Gateway diversity, peering, redundancy	Stiri et al. (2026)
Local access	4G/5G, Wi-Fi, FWA, LPWAN, D2D	Connect people and devices affordably	Density, mobility, terrain, device ecosystem	Lin et al. (2021); ITU (2025)

National Conference on Emerging Trends in Arts, Humanities and Multidisciplinary Research (NCETAHMR)


Organized by- Navyug College of Education, Hisar (16 Aug 2026)

In IJESH ISSN: 2250-3115

Edge & services	Cache, local compute, app gateways	Reduce backhaul and sustain local services	Cache ratio, service priority, local autonomy	Chen et al. (2024); Hu (2024)
Energy & physical	Solar, battery, shelters, grounding	Maintain operation without reliable grid	Autonomy, climate, load, maintenance	ITU (2025)
Operations & security	Monitoring, patching, IAM, spares	Reliability, cyber resilience, repair	MTTR, update status, access control	Hu (2024); Mahboob & Liu (2024)
Governance & affordability	Licensing, spectrum, tariffs, subsidy	Sustainable and inclusive service	Price, SLA, competition, privacy, skills	ITU (2025); McMahon et al. (2025)
Cross-layer orchestration	Policy engine, telemetry, SDN/analytics	Choose best resource per service state	Latency, cost, energy, security, priority	Kodheli et al. (2021); Mahboob & Liu (2024)

Source: Author's framework informed by Kodheli et al., 104

Cross-layer orchestration is the fusion of all seven layers. It is possible to select different paths, such as terrestrial, GEO, MEO, LEO, depending on the requirements of the application and the real-time conditions, using a policy engine. Telemedicine video can be transmitted on the lowest latency path possible; background software updates can be sent via less costly bulk capacity; emergency traffic can be replicated over two paths; and nonessential traffic can be throttled in battery stress. This type of programmable multi-connectivity can be interpreted as a part of the overall trend towards software-defined and intelligent satellite networking as discussed in contemporary satellite-communication research (Kodheli et al., 104). The integrated architecture is designed to be vendor neutral. Governments and operators should be free to mix and match commercial LEO broadband, regional GEO capacity, mobile-network infrastructure, community networks and standards-based NTN as local circumstances evolve.



Open IP interfaces, interoperable monitoring, standards-based authentication and portable service policies minimize lock-in and enable future migration. This is particularly significant because the

National Conference on Emerging Trends in Arts, Humanities and Multidisciplinary Research (NCETAHMR)

Organized by- Navyug College of Education, Hisar (16 Aug 2026)


In IJESH ISSN: 2250-3115

rural networks generally operate for a long time, and constellations, pricing, licenses and terminal technology can change over that period.

Digital Access and Service Delivery in Rural and Remote Regions

The usefulness of the framework becomes apparent when it comes to service delivery. Bandwidth, latency, continuity and affordability needs vary depending on the industry requiring educational, healthcare, agriculture, public administration, emergency response and local enterprise solutions. Rather than create a single rural broadband service, the framework establishes service classes and then provides a mapping of classes to network resources. This saves cost because applications that actually need low latency capacity do not use the higher cost link, while delay-tolerant traffic can be cached, scheduled, compressed, or sent via a lower cost link. Shared backhaul and caching at the local level are very advantageous for digital education. A school can be an anchor for community connectivity, which includes live classes, assessment, teacher training, cloud platforms, and content synchronization, running on satellite broadband. The larger instructional videos and software programs can be stored on the local file system and then sent to dozens of students over the satellite link without having to repeatedly download the same files. The education investment can be leveraged to help families outside of school hours when community Wi-Fi or cellular network extends beyond the school. The service delivery model is thus to integrate institution-grade backhaul with demand aggregation, rather than view each student as a stand-alone broadband endpoint. Agricultural service delivery: a blend of broadband and IoT. Large farms, extension services and cooperatives can benefit from broadband for video, market platforms, imagery, machinery support and cloud applications, and distributed sensors only need low rate, energy efficient connectivity. Cioni et al. demonstrate how satellite IoT can provide sensing in large areas beyond the terrestrial reach of sensing networks, and explore the trade-offs between power, coverage, spectrum, standards, and satellite altitude (Cioni et al., 1720). The integrated framework thus leverages LPWAN or satellite IoT for field sensing and broadband backhaul for media-rich applications, rather than traffic from all agricultural applications being sent through the same interface.

Image 3: Satellite-Enabled Digital Access and Service Delivery in Rural and Remote Communities



The connected community center, local administration center and public kiosks can be used to

National Conference on Emerging Trends in Arts, Humanities and Multidisciplinary Research (NCETAHMR)

Organized by- Navyug College of Education, Hisar (16 Aug 2026)

In IJESH ISSN: 2250-3115

enhance e-government services. Digital identity support, applications for benefits, land records, tax services, licensing, banking and submitting documents are all services that remote citizens might require. A shared satellite-supported public access point can decrease travelling distances to district centres, but the security and privacy needs are high. Government traffic should be tunneled using encryption, employ robust authentication, limit administrative devices, and rely on resilient local power. There are also metrics other than raw network throughput that can be used to measure performance: successful completion of transactions and readiness of citizen services. Yet another use case is emergency/disaster communication. Floods, storms, earthquakes, wildfire, landslides or infrastructure damage can cut off terrestrial communication networks at the time it is most needed. The use of satellite paths means they include geographic diversity as they are not reliant on the same fibre or tower chain. Consideration of a rural emergency architecture ought, then, to include portable terminals, battery reserves, backup configurations and, if possible, direct-to-device. The critical messages can be duplicated over multiple paths and lower priority traffic can be suspended. The integrated model is of the emergency connectivity as a permanent resilience capability, and not as an ad-hoc solution to be deployed in the event of failure.

Table 3. Service-Delivery Requirements and Recommended Integrated Connectivity Strategy

Service	Traffic/performance need	Recommended strategy	Primary success indicator
Digital education	Video, downloads, cloud learning	Shared LEO/GEO backhaul + Wi-Fi + local cache	Class continuity and content availability
Telemedicine	Stable two-way video, secure records	Low-latency primary path + satellite/terrestrial fallback	Consultation completion and uptime
Agriculture	Sensors + periodic broadband media	Satellite IoT/LPWAN + broadband aggregation	Coverage, sensor delivery and advisory access
E-government	Secure transactions and document transfer	Community/public terminal + encrypted backhaul	Successful transaction rate
Emergency response	Voice, alerts, messaging, coordination	Dual-path TN/NTN + battery reserve + D2D	Availability during terrestrial outage
Rural enterprise	Payments, cloud, video, logistics	Dedicated/shared broadband + QoS	Business uptime and transaction reliability

Source: Research synthesis based on Cioni et al., 1720

National Conference on Emerging Trends in Arts, Humanities and Multidisciplinary Research (NCETAHMR)

Organized by- Navyug College of Education, Hisar (16 Aug 2026)

In IJESH ISSN: 2250-3115

Recurring demand can be generated by local enterprise or distance working to make rural broadband financially sustainable. Tourism operators, the farms, logistics companies, shops, financial agents and small businesses require payments, cloud software, communications, e-commerce and access to supply chains. There is some level of willingness to pay in the household sector, but there is also some level of anchor revenue in the form of demand from businesses and institutions. The rural-connectivity work of the ITU focuses on the necessity for sustainable business models, infrastructure sharing and locally relevant financing to ensure services on the long run (ITU, 17). The framework thus promotes multi-user bases, not only household based. Empirical evidence also demonstrates that quality satellite service can improve digital participation without doing anything to address other inequalities. McMahon et al. (article 102912) conclude that LEO connectivity in remote Indigenous communities in northern Canada was found to enhance speed, reliability and online participation over previous options, but that affordability, proprietary equipment, service reliability, and lack of local technical support were still important concerns.

Implementation Challenges

The primary implementation obstacle is cost. Capacity and terminals are more competitive via satellite, but in many areas, the income of rural households is still low and the installation price may still be high. The total cost of owning the terminal must cover the cost of the terminal, local access equipment, power systems, installation travel, satellite subscription, spectrum regulator fees, parts and materials, technical support, cyber security maintenance and eventual replacement. Shared backhaul can lower the cost per user and subsidies can be targeted to schools, clinics and other places of community access where they generate wide social value. The cost of the product should not be the sole factor to consider when measuring affordability, but also as a proportion of local income. The second challenge is the spectrum and regulatory coordination. Satellites services are available over several bands and have to share the airwaves with terrestrial systems and other satellite services. Direct-to-cell makes things more complicated because of the possibility that satellite and mobile services could share or border the same spectrum over a vast geographical region. As the Broadband Commission (2025) points out, policy and regulatory frameworks need to change to keep up with the development of NTN and direct-to-cell. 16. Spectrum rules, gateway approval, terminal authorization and predictable licensing can reduce deployment delay and expense in out-of-the-way areas significantly. Power and environmental reliability is the third challenge. Weaker grids, fuel delivery concerns, high temperatures, dust, snow, storms or seasonal access restrictions can be a problem at remote sites. Energy systems can be sized to operate autonomously, with the help of solar generation and battery storage, but they need to be designed to meet worst case scenarios, not average sunshine. Power monitoring needs to be linked with network telemetry to ensure that load can be controlled before batteries reach critical levels. Energy-aware service policies are particularly beneficial for IoT gateways, edge servers, and redundant radios that are not all required to be active all the time. The fourth challenge is "operational capacity. Many of the outages in the field are due to local problems, which are not necessarily caused by the satellites: damage to cables, water entering the system, battery

National Conference on Emerging Trends in Arts, Humanities and Multidisciplinary Research (NCETAHMR)

Organized by- Navyug College of Education, Hisar (16 Aug 2026)

In IJESH ISSN: 2250-3115

failure, loose connectors, misconfiguration of routers, blocked antennas, and failed power supplies are just a few of the issues that can cause an outage.

Conclusion

This paper has designed a more integrated framework of satellite communication to enhance the digital access and service provision in the remote and rural areas. The analysis reveals that satellite communication is best used as part of a wider service architecture and cannot be used as a replacement for the terrestrial infrastructure. The proposed seven-layer architecture includes space resources, gateway and transport infrastructure, local access, edge and service platforms, energy systems, operations and security, and governance and affordability and is orchestrated by a cross-layer function. This architecture enables the deployment of GEO, MEO, LEO, fibre, microwave, 4G/5G, Wi-Fi, fixed wireless, direct-to-device, and satellite IoT resources to satisfy a variety of needs, including education, healthcare, agriculture, e-government, emergency response and local enterprise. The study also shows that radio cannot create meaningful connectivity in the rural areas without considering the factors that influence it. Whether a satellite project is a viable public service depends on three factors: affordability, renewable energy, local technical capacity, gateway diversity, cyber security, terminal interoperability, transparent spectrum rules, community participation, and measurable service level obligations. Historical distinction between satellite and mobile networks is being blurred as a result of current NTN standardization and the emergence of direct-to-cell (DTC) services, and modern multi-orbit systems offer new opportunities for performance and resilience. Concurrently, these advances drive the demand for open interfaces, harmonized regulation, responsible utilization of the spectrum and flexibility over the long term. The key policy takeaway is that the goal of evaluating rural broadband programs on service outcomes not infrastructure counts. A successful programme is one in which students can learn, patients can complete consultations, farmers can get information when they need it, citizens can avail of digital government services, businesses can stay connected and communities can stay in touch during emergencies – at an affordable cost. Future studies should thus involve a multi-faceted combination of application-level field measurements with cost, energy, inclusion and resilience indicators. A hybrid, service-aware satellite framework can be an economically viable means to lessen the geographic penalty of remote populations and improve digital access into service delivery that is both reliable and meaningful.

References

- Broadband Commission for Sustainable Development. (2025). The State of Satellite Broadband 2025. International Telecommunication Union.
- Chen, Y., Ma, X., & Wu, C. (2024). The concept, technical architecture, applications and impacts of satellite internet: A systematic literature review. *Heliyon*, 10(13), e33793. <https://doi.org/10.1016/j.heliyon.2024.e33793>
- Cioni, S., et al. (2021). A survey on technologies, standards and open challenges in satellite IoT. *IEEE Communications Surveys & Tutorials*, 23(3), 1693–1720. <https://doi.org/10.1109/COMST.2021.3078433>

***National Conference on Emerging Trends in Arts, Humanities and
Multidisciplinary Research (NCETAHMR)***

Organized by- Navyug College of Education, Hisar (16 Aug 2026)

In IJESH ISSN: 2250-3115

- Hu, P. (2024). Closing the performance and management gaps with satellite Internet: Challenges, approaches, and future directions. arXiv:2401.07842, pp. 1–18.
- International Telecommunication Union (ITU). (2025a). Telecommunications/ICTs for Rural and Remote Areas: Output Report on ITU-D Question 5/1. Geneva: ITU.
- Kodheli, O., Lagunas, E., Maturo, N., Sharma, S. K., Shankar, B., Montoya, J. F. M., Duncan, J. C. M., Spano, D., Chatzinotas, S., Kisseleff, S., Querol, J., Lei, L., Vu, T. X., & Goussetis, G. (2021). Satellite communications in the new space era: A survey and future challenges. *IEEE Communications Surveys & Tutorials*, 23(1), 70–109. <https://doi.org/10.1109/COMST.2020.3028247>
- Lin, X., Rommer, S., Euler, S., Yavuz, E. A., & Karlsson, R. S. (2021). 5G from space: An overview of 3GPP non-terrestrial networks. *IEEE Communications Standards Magazine*, 5(4), 147–153. <https://doi.org/10.1109/MCOMSTD.011.2100038>
- Mahboob, S., & Liu, L. (2024). Revolutionizing future connectivity: A contemporary survey on AI-empowered satellite-based non-terrestrial networks in 6G. *IEEE Communications Surveys & Tutorials*, 26(2), 1279–1304.
- McMahon, R., Akçayır, M., Norris, B., & Fabian, L. (2025). Assessing the impacts of low-earth orbital satellite systems in remote Indigenous communities: Social and economic outcomes of use in northern Canada. *Telecommunications Policy*, 49(2), 102912. <https://doi.org/10.1016/j.telpol.2025.102912>
- Stiri, S., Palattella, M. R., Nieves Castano, J. D., & Politis, C. (2026). Satellite backhaul for extending connectivity in rural remote areas: Deployment and performance assessment. *Network*, 6(1), 12, pp. 1–20. <https://doi.org/10.3390/network6010012>
- 3rd Generation Partnership Project (3GPP). (2022). Release 17: Non-terrestrial network related specifications and enhancements. 3GPP.